



Specifications Ledvance LED Panel  
Linear Indiviled Direct 1500 52W  
6050lm - 930 Warm White | 150x12cm  
- UGR <19 - Emergency

[View Product](#)

General Information

|                          |                                                                |
|--------------------------|----------------------------------------------------------------|
| SKU                      | 256318                                                         |
| EAN                      | 4099854249730                                                  |
| Brand                    | Ledvance                                                       |
| Manufacturer Name        | LINEAR INDIVILED DIRECT 1500 EMERGENCY 1500 P 52W 930 PS EL WT |
| Any Lamp all-in warranty | 5 Years                                                        |
| Average Lifetime (h)     | 100000                                                         |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x58            |
| Wattage                     | 52              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 930 Warm White  |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra)       | 90-99           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 6050            |
| Luminous Efficacy (lm/W)    | 116             |

|                        |                |
|------------------------|----------------|
| IP-rating              | IP20           |
| Impact Protection (IK) | IK06 - 1 joule |
| Power factor           | >0.90          |
| Product Type Category  | LED Panel      |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Ceiling                        |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | Plastic                        |
| Operating Temperature | 0 to +40                       |
| Emergency Lighting    | Optional: Emergency Light      |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 150x12cm |
| Length (mm)    | 1475     |
| Width (mm)     | 125      |
| Height (mm)    | 43       |

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

**Why Any-lamp?**



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

