



Specifications Sylvania LED Downlight  
Insaver Slim 150 Aluminium White  
9.5W 1150lm 70D - 830 Warm White |  
Cutout 150mm - IP44 - Dimmable



[View Product](#)

## General Information

|                          |                             |
|--------------------------|-----------------------------|
| SKU                      | 255240                      |
| EAN                      | 5410288305349               |
| Brand                    | Sylvania                    |
| Manufacturer Name        | INSV SL U19 IP44 DL 150 830 |
| Any Lamp all-in warranty | 5 Years                     |
| Average Lifetime (h)     | 100000                      |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Emergency Lighting          | No Emergency Unit  |
| Tiltable                    | No                 |
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 1x18               |
| Wattage                     | 9.5                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |

|                          |                                |
|--------------------------|--------------------------------|
| Beam Angle (degree)      | 70                             |
| Luminous Flux (Lumen)    | 1150                           |
| Luminous Efficacy (lm/W) | 121.1                          |
| Power factor             | >0.97                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 150                    |
| IP-rating              | IP44                   |
| Impact Protection (IK) | IK07 - 2 joules        |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 50  |
| Diameter (mm) | 165 |

## Sensor Information

Type of sensor

### Why Any-lamp?

No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process